


Desktop Rewrite Card Printer

S20R



Front end



Top end



Back end

Multi-functional option module to support various card printing

- Dual interface card encoding module
- Contactless ID Card encoding module
- UHF chip card encoding module
- Magnetic stripe card encoding module

Lightweight body, Reliability and Easy-to-Use

- Advanced thermal dye-sublimation printing technology
- Continuous printing of cards and time-saving effort
- Simple operation interface and easy-to-use
- Lightweight and easy to maintain
- Low noise in printing process
- High Printing Speed Engine

Features

- Compact and lightweight body
- Support single-sided printing
- Rewrite card Printing
- Support hand-feeding

SEAORY S



Come with professional printing software

Technical Parameter

Model	S20R/Desktop Rewrite Card Printer
Specifications	244 × 160 × 208 (mm), 4.5Kg
Interfaces	USB
Input Capacity	--
Output Capacity	--
Print Speed	Rewrite card printer erasing speed: 6s per card
Card Material	PVC / Composite PVC / Rewritable thermochromic cards
Power	AC 100~240V, 50/60 Hz, DC 24-25.5V, 2.7 A
Print Dimension	ISO CR80 (53.98mm×85.60mm), edge-to-edge printing
Print Resolution	300dpi × 300dpi (300 dpi × 600 dpi, 300 dpi × 1200 dpi print resolution optional)
Memory	128MB
Print Method	Sublimation (Direct-to-card)
Card Thickness	0.3-1.05mm
LCM Display	Rewrite card printer erasing speed: 6s per card
Operation System	Support Windows XP/7/8/10/11, Windows Server 2003/2008/2012/2016; Linux; Android; Support NeoKylin,Kylin, UOS and other made-in-china operating system
Warranty	Card printer : 24 months (artificial damage excluded) / Print head: Replace one for free within 1 year (artificial damage excluded)
Operating Condition	1. Regular running temp.: 15°C-30°C(59-86°F), 20%~65% RH non-condensing 2. Lowest / Highest running temp.: 0°C(32°F) / 40°C(104°F), 20%~65% RH non-condensing
Storage Condition	Temp.: -5°C-70°C(23-158°F), 20%~70% RH non-condensing
Certificates	CCC, FCC, CE, ROHS, BIS

