



TPL80H

3inch Thermal Printer

Battery detachable

Support for self-service upgrades

Support multi-language

Can print continuously for 5 hours

Application Scenarios:

Delivery orders, traffic police fines, parking fee receipts printing, etc.

80H

Portable Label Printer

Performance	Print Method	Thermal Line Printing
	Print Width	72MM
	Resolution	8 dot/mm (203dpi)
	Print Speed	50 ~ 80mm/s
	Print	12.5% printing density can print 100 ~ 200m, 25% printing density can print 80 ~ 100m, this parameter is for reference only
	Character	Chinese characters (support GBK), international character set, ascii characters, several half-width custom characters.
	Character Size	18*16、16*16、8*16、9*24、12*24
	Number of Columns	3 Line/S
Paper	Width	80MM±0.5MM
		≤40mm
	Thickness	0.08-0.16mm
Print Content	Barcode Type	CODE39、EAN13、CODABAR、CODE93、ITF、CODE128、QR Code、PDF417
		0 CP437 [US, European Standard]; 2 CP850 [Multilingual] (Spanish); 3 CP860 [Portuguese] 4 CP863 [Canada-France]; 5 CP865 [Nordic]; 6 WCP1251 [Cyrillic 7 CP866 Cyrillic #2; 8 MIK [Cyrillic/Bulgarian]; 9 CP755 [Eastern Europe, Latvian 2]; 11 Pashto; 12 Persian; 13 Vietnamese; 15 CP862 [Hebrew]; 16 WCCP1252 Latin I; 17 WCP1253 [Greek]; 18 CP852 [Latin 2]; 22 CP864 [Arabic]; 27 CP720 [Arabic]; 30 WCP1250 [Central Europe]; 34 WCP1256 [Arabic]; 35 WCP1258 [Vietnam]; 40 iso-8859-6 [arabic]
Physical	Print Head	50KM
	Interface	USB micro ; 2.0 Bluetooth+4.0 Bluetooth
	Paper Detect	The printer function indicator (red light) flashes when the paper runs out, and the buzzer will sound.
	Print Command	TSPL/CPCL/ESC/POS
	Power Supply	2600MAH Rechargeable
	Dimension	130*115*60mm
	Net Weight	372.4g
Environmental	Operating	-10°C-50°C

80H

Portable Label Printer

	Temperature	
	Storage Temperature	15°C-20°C
	Operating Humidity	20%-85%
	Storage Humidity	45%-75%

**Test conditions: ambient temperature=23 °C;

**Test conditions: ambient humidity=

Specifications are subject to change without prior notice

Version: 2021/8/17 V1.0.1