

AUTOID Pad Air

All-in-one industrial design, stylish, lightweight, and slim

The ideal product combines consumer appeal with industrial protection. Displays colors with precision and delicacy on the 10.1-inch screen with 1080P resolution. It is equipped with a 2.2GHz octa-core processor that provides remarkable performance and efficiency, also as durable to sustained harsh environment.



Product Features



High-efficient data transmission and data processing

Upgrade 2.2GHz 7nm CPU, faster data and image/graphics processing ability, faster wireless connection, and faster and more stable data transmission
Bluetooth 5.0 can connect to Bluetooth peripherals, such as scanners, headphones, printers, and more, with twice the processor speed, four times the range, and lower power consumption than Bluetooth 4.0.



10140mAh battery can last all day

Battery work can last all day without charging. Power-saving technology combined with artificial intelligence offers more than 30% power savings with this lithium-ion battery. By using optional PD30W fast charging technology, the battery can be charged by 80% in 2 hours.

Specifications

tics
10.1 in. L x 6.8 in. W x 0.5 in. H
258 mm L x 173 mm W x 11.6 mm H
25.9oz/735g, standard model, without fingerprint,
normal brightness, without hand strap, including
scan engine
10.1-inch full view LCD display screen, capacitive 10
point touch, supporting glove mode, FHD (1920 x
1200)
Capacitive touch, support touch-with or without a
thick glove/with dry or wet hand
Bottom contact interface DC IN: Maximum 27W,
non-removable 10140mAH rechargeable Li-ion
battery Rating 9800mAh,
Bottom contact interface: USB2.0, UART, DC
input/output (maximum input power 18W), I/O
Micro SD Card, maximum no less than 128GB
TYPE-C interface (supporting USB2.0)
Bottom contact interface: USB2.0, UART, DC
input/output, I/O
Three color light (red, green, blue). Scanning red
light, Charging red light, Full charged green light,
reserved blue light
3 keys including power on/off, volume+ and Volume
-
Built-in dual stereo speaker, 4Ω2W*2, built-in dual
microphone, support Type-C digital headphone.
Will support it in the future
cteristics
Octa-Core 2.2GHz
Android 12
RAM: LPDDR4X SDRAM 4GB (8GB compatible)
RAM: LPDDR4X SDRAM 4GB (8GB compatible) ROM: 64GB UFS (Optional 128GB compatible)
RAM: LPDDR4X SDRAM 4GB (8GB compatible) ROM: 64GB UFS (Optional 128GB compatible) -4 °F to 122 °F/-20 °C to +50 °C
RAM: LPDDR4X SDRAM 4GB (8GB compatible) ROM: 64GB UFS (Optional 128GB compatible) -4 °F to 122 °F/-20 °C to +50 °C Battery included: -4 °F to 140 °F/-20 °C to +60 °C
RAM: LPDDR4X SDRAM 4GB (8GB compatible) ROM: 64GB UFS (Optional 128GB compatible) -4 °F to 122 °F/-20 °C to +50 °C Battery included: -4 °F to 140 °F/-20 °C to +60 °C 5% to 95% RH non-condensing
RAM: LPDDR4X SDRAM 4GB (8GB compatible) ROM: 64GB UFS (Optional 128GB compatible) -4 °F to 122 °F/-20 °C to +50 °C Battery included: -4 °F to 140 °F/-20 °C to +60 °C 5% to 95% RH non-condensing 3.9 ft./1.2 m drops to marble at room temperature
RAM: LPDDR4X SDRAM 4GB (8GB compatible) ROM: 64GB UFS (Optional 128GB compatible) -4 °F to 122 °F/-20 °C to +50 °C Battery included: -4 °F to 140 °F/-20 °C to +60 °C 5% to 95% RH non-condensing 3.9 ft./1.2 m drops to marble at room temperature IP65
RAM: LPDDR4X SDRAM 4GB (8GB compatible) ROM: 64GB UFS (Optional 128GB compatible) -4 °F to 122 °F/-20 °C to +50 °C Battery included: -4 °F to 140 °F/-20 °C to +60 °C 5% to 95% RH non-condensing 3.9 ft./1.2 m drops to marble at room temperature
RAM: LPDDR4X SDRAM 4GB (8GB compatible) ROM: 64GB UFS (Optional 128GB compatible) -4 °F to 122 °F/-20 °C to +50 °C Battery included: -4 °F to 140 °F/-20 °C to +60 °C 5% to 95% RH non-condensing 3.9 ft./1.2 m drops to marble at room temperature IP65 ±15 kV air discharge, ±8 kV direct discharge
RAM: LPDDR4X SDRAM 4GB (8GB compatible) ROM: 64GB UFS (Optional 128GB compatible) -4 °F to 122 °F/-20 °C to +50 °C Battery included: -4 °F to 140 °F/-20 °C to +60 °C 5% to 95% RH non-condensing 3.9 ft./1.2 m drops to marble at room temperature IP65
RAM: LPDDR4X SDRAM 4GB (8GB compatible) ROM: 64GB UFS (Optional 128GB compatible) -4 °F to 122 °F/-20 °C to +50 °C Battery included: -4 °F to 140 °F/-20 °C to +60 °C 5% to 95% RH non-condensing 3.9 ft./1.2 m drops to marble at room temperature IP65 ±15 kV air discharge, ±8 kV direct discharge G-Sensor, L-Sensor, Eectronic compass, Gyroscope
RAM: LPDDR4X SDRAM 4GB (8GB compatible) ROM: 64GB UFS (Optional 128GB compatible) -4 °F to 122 °F/-20 °C to +50 °C Battery included: -4 °F to 140 °F/-20 °C to +60 °C 5% to 95% RH non-condensing 3.9 ft./1.2 m drops to marble at room temperature IP65 ±15 kV air discharge, ±8 kV direct discharge G-Sensor, L-Sensor, Eectronic compass, Gyroscope Seuic 2D image scan engine
RAM: LPDDR4X SDRAM 4GB (8GB compatible) ROM: 64GB UFS (Optional 128GB compatible) -4 °F to 122 °F/-20 °C to +50 °C Battery included: -4 °F to 140 °F/-20 °C to +60 °C 5% to 95% RH non-condensing 3.9 ft./1.2 m drops to marble at room temperature IP65 ±15 kV air discharge, ±8 kV direct discharge G-Sensor, L-Sensor, Eectronic compass, Gyroscope Seuic 2D image scan engine Front: 5 MP fixed focus
RAM: LPDDR4X SDRAM 4GB (8GB compatible) ROM: 64GB UFS (Optional 128GB compatible) -4 °F to 122 °F/-20 °C to +50 °C Battery included: -4 °F to 140 °F/-20 °C to +60 °C 5% to 95% RH non-condensing 3.9 ft./1.2 m drops to marble at room temperature IP65 ±15 kV air discharge, ±8 kV direct discharge G-Sensor, L-Sensor, Eectronic compass, Gyroscope Seuic 2D image scan engine

	(Mifare one S50, S70 and Other compatible);
	Support NFC protocol; Support for
	second-generation ID cards
	HF frequency band 13.56MHz;
	Reading distance 0~6cm (ISO15693), 0-4cm
	(ISO14443A/B) (varies by the labels)
Wireless Connectivi	ty
WLAN Radio	IEEE 802.11a/b/g/n/d/e/h/i/j/k/r/v/ac (2.4G/5G
WLAIN NAUIU	dual-frequency WIFI)
Data Rates	802.11a: 6, 9, 12, 18, 24, 36, 48, 54Mbps
	802.11b: 1, 2, 5.5, 11Mbps
	802.11g: 6, 9, 12, 18, 24, 36, 48, 54Mbps
	802.11n:6.5, 13, 19.5, 26, 39, 52, 58.5, 65Mbps
	(20MHz, Long GI, 800ns)
	802.11n: 7.2, 14.4, 21.7, 28.9, 43.3, 57.8,
	65,72.2Mbps (20MHz, short GI, 400ns)
	802.11n : 32.5 /65 /97.5 /130 /195 /260 /292.5
	/325/390/433.3Mbps (80MHZ, GI=400ns)
Working Channel	CH1~CH13, CH34~CH140, CH149~CH165
Security of WLAN	OPEN, WEP, WPA2-PSK(TKIP+AES), TLS, TTLS
Security of WLAN	(MS-CHAP), TTLS (MS-CHAP v2), TTLS(CHAP),
	TTLSMD5, TTLS-PAP, PEAP-TLS, PEAP (MS-CHAP v2),
	AES etc.
WWAN	ALS etc.
WWAN Radio	GSM: B2/B3/B5/B8
WWWAIN NAUIO	TD-SCDMA: B34/B39
	WCDMA: B1/B5/B8
	TDD-LTE: B34/B38/B39/B40/B41
	FDD-LTE: B1/B3/B5/B7/B8/B20/B28a&b
	NR: N1/N3/N28/N41/N77/N78/N79
Positioning	GPS+GLONASS+ BeiDou, support AGPS;
	Frequency: GPS: L1(1.575GHz);
	Beidou Navigation: B1(1.561GHz);
	GLONASS: L1(1.602GHZ)
14/0441	Precision: 5-10meter (OPEN SKY)
WPAN	
Bluetooth	Bluetooth 5.0
.	Transmission >20m (industrial-grade Bluetooth)
Accessories	
Standard	Adapter × 1, USB cable × 1, Hand Strap × 1
Additional	Fast Charging Adapter, Dual Type-C Cable,
	Single-slot Charging Cradle, Multifunctional
	Single-slot Charging Cradle, Silicone Protective Case,
	Tempered Screen Protector, Shoulder Belt, Fixed
	Bracket, Multifunctional Docking, Stylus
Third Party Applicat	
	ion Development Support
System Software	Android 12.0





